



China abec 5 Bearings Supplier



6001 Bearing 2D drawings and 3D CAD models

Best price NSK deep groove ball bearings 6001
6301 6202 6203 6305 DDU ZZ C3 NSK ball
bearing for Cambodia

Bearing No. 6001

| | |
|----------------------------------|--------------------------|
| Size | 12x28x8 mm |
| Bore Diameter | 12 mm |
| Outer Diameter | 28 mm |
| Width | 8 mm |
| d | 12 mm |
| D | 28 mm |
| B | 8 mm |
| C | 8 mm |
| r min. | 0,3 mm |
| da min. | 14 mm |
| da max | 15,5 mm |
| Da max. | 26 mm |
| ra max. | 0,3 mm |
| Weight | 0,022 Kg |
| Basic dynamic load rating (C) | 5,1 kN |
| Basic static load rating (C0) | 2,37 kN |
| (Grease) Lubrication Speed | 28 000 r/min |
| (Oil) Lubrication Speed | 32 000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.02 |
| EAN | 0029176012235 |



China abec 5 Bearings Supplier

| | |
|---------------------------------|---|
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 12MM Bore; 28MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 6001 |
| Weight / LBS | 0.05 |
| Outer Race Width | 0.315 Inch 8 Millimeter |
| Outside Diameter | 1.102 Inch 28 Millimeter |
| Bore | 0.472 Inch 12 Millimeter |
| SRI | 2.46 |
| hidYobi | 6001 |
| LangID | 1 |
| D_ | 28 |
| SREX | 0.015 |



China abec 5 Bearings Supplier

| | |
|------------|-------------|
| B_ | 8 |
| da min | 14 |
| hidTable | ecat_NSRDGB |
| Oil rpm | 32000 |
| SRE | 2.46 |
| mass | 0.022 |
| GRS rpm | 28000 |
| ra | 0.3 |
| SRIX | 0.015 |
| D_a | 26 |
| SRIN | -0.015 |
| C0 | 2.37 |
| fo | 13 |
| SREN | -0.015 |
| DE_ | 24.762 |
| Prod_Type3 | DGBB_SR_OT |
| DA_ | 4.762 |
| bomp | 0 |
| Z_ | 8 |
| yobi | 6001 |
| C_conv | 5100 |
| ALPHA_ | 0 |
| SDM_ | 20 |
| r | 0.3 |
| KBRG | 6101 |
| SBRG | 10 |
| DI_ | 15.238 |